

SHAKER

The optimum performance **SHAKER** with user-friendly function & excellent construction to maximize effectiveness of your invaluable test process.



F

eature

- * Brushless DC Motor
- * Shaking Orbital Motion
- * Safety Device
- * Digital PID controller
- * Universal spring rack(OPTION).

Model	FTSK-350	F FTSK-450	FTSK-750
Speed Range	Max. 350 rpm		
Speed controller	LED Digital controller		
Display	Digital display		
Timer	99hr 59min		
Motion	Orbital		
Motor	Blussless DC motor		
Drive system	Beltless direct drive		
Dimensions	350x350x110mm	450x450x120 mm	750x500x120 mm
Capacity	250 ml x 9ea	250 ml x 25ea	250 ml x 40ea
Tray (size)	190x400x25 mm	240x480x30 mm	240x770x30 mm
Power supply	AC 220V, 1Ø 50/60 Hz		
Weight			

Optional Accessories

Capacity	FTSK-350	FTSK-450	FTSK-750
100ml Flask	16	36	60
250ml Flask	9	25	40
500ml Flask	9	16	24
1000ml Flask	4	9	15
2000ml Flask	2	4	8
Dimensions	350x350mm	450x450 mm	750x500 mm
Capacity	350x350 mm	450x450 mm	750x500 mm